Skuteriai Limited - 31A Market Place
Boston, PE21 6EH, UK
Įmonės kodas: 10524118
SKUTERIAI LIMITED
LT823500010006095589
Paysera LT, UAB
SWIFT/BIC CODE: EVIULT21XXX

Telefonas: +37060902099 - El. paštas: info@skuteriai.lt

IntAct BP 12V 50Ah AGM akumuliatorius



Prekės ženklas: INTACT
Sandelyje: 6
Svoris: 14.50kg
Matmenys: 197.00mm x 165.00mm x 170.00mm



Kaina: 129.00€

Aprašymas
intAct BP12-50 duomenų lapas


- Informacija
- Gamintojas: INTACT (Vokietija)
- Talpa: 50Ah
- Įtampa: 12V
- Akumuliatoriaus tipas: VRLA (AGM)
- Gnybtų padėtis: -- +
- Korpuso dydis: SLA 12-40 (~198x165x170)
- Ilgis (mm): 197
- Plotis (mm): 165
- Aukštis (mm): 170
- Svoris (kg): 14.5
- Garantija: 6 mėnesiai

BP12-50(12V50AH)



Dimensions (mm)	Standard Terminal (mm) Threaded Insert 6mm STUD
	T6 


Discharging Current & Discharge Duration Time



PHYSICAL SPECIFICATION

Nominal Voltage Nominal Capacity (10HR)		12V 50AH
Dimension	Length Width Container Height Total Height (with Cover)	197±2mm (7.76 inches) 165±2mm (6.50 inches) 170±2mm (6.69 inches) 170±2mm (6.69 inches)
Weight		Approx 14.5kg (31.97lbs)
Standard Terminal		Threaded Insert 6mm STUD

Discharge Characteristics (25°C,77°F)



Electrical Specification

Rated Capacity	20 hour rate (2.50A) 10 hour rate (4.80A) 5 hour rate (8.29A) 3 hour rate (12.5A) 1 hour rate (29.5A)	50.0AH 48.0AH 41.4AH 37.5AH 29.5AH	Constant-Voltage Charge	Cycle	Initial Charging Current less than 15.0A.Voltage 14.4V~ 15.0V at 25°C (77°F) Temp. Coefficient -30mV/°C
Capacity affected by Temperature	40°C (104°F) 25°C (77°F) 0°C (32°F)	103% 100% 86%		Standby	No limit on Initial Charging Current Voltage 13.5V~13.8V at 25°C(77°F) Temp. Coefficient - 20mV/°C

Constant Current (Amp) and Constant Power (Watt) Discharge Table (25° C,77° F)

Time(minute) / Final voltage / Amp/Watt/Cell	10 1.30	15 1.30	20 1.30	30 1.60	45 1.60	60 1.67	120 1.70	180 1.75	240 1.75	300 1.75	360 1.75	480 1.80	600 1.80	1200 1.80
A	117.4	89.26	70.46	52.05	37.21	29.40	17.0	12.5	10.2	8.29	7.32	5.735	4.8	2.50
W	199.6	156.1	126.4	94.90	69.02	96.67	32.63	24.2	19.7	16.0	14.3	11.32	9.543	4.964