Skuteriai Limited - 31A Market Place
Boston, PE21 6EH, UK
Įmonės kodas: 10524118
SKUTERIAI LIMITED
LT823500010006095589
Paysera LT, UAB
SWIFT/BIC CODE: EVIULT21XXX

Telefonas: +37060902099 - El. paštas: info@skuteriai.lt

Etac Nova 500



Prekės ženklas: MOLIFT
Sandelyje: 2
Svoris: 0.00kg
Matmenys: 0.00cm x 0.00cm x 0.00cm

Kaina: 470.00€

Trumpas aprašymas
Dėl pirkimo ir pristatymo sąlygu kreipkitės telefonu +37060902099

Aprašymas
Naudotas Etac Nova 500 mobilus keltuvas skirtas pastatyti ar perkelti ligonį nuo lovos į vežimėlį, iš vežimėlio į lovą, ant tualeto kėdės ir pan. Elektriniu būdu (distancinio valdymo pulteliu) atliekamas kėlimas aukštyn-žemyn ir važiuoklės valdymas. Kaina 470 EUR.

Keliamoji galia iki 180 kg.

Į komplektacija įeina keltuvas, baterijos (baterijos patikrintos ir yra kaip naujos), įkroviklis, kėlimo diržas.

Technical Data

Safe Working Load (SWL)
180 kg (395 lbs)

Weight of unit
Total weight: 46 kg (101 lbs)
Chassis/Base: 13 kg (28½ lbs)
Lifting column/Mast: 23 kg (51 lbs)
Footrest incl. leg support: 10 kg (22 lbs)

Operating voltage:
24V DC

Power supply:
Battery power

Power consumption:
10A

Protection class:
Motor IPX4
Electrical box IPX4
Hand control IPX4

Sound volume:
53 dBA

Operating forces button
max 5 N


Material:
Powder-coated steel, Plastic


Turning radius:
approx. 110 cm (43½")

Number of lifts with fully charged battery:
80 lifts (80 kg / 175 lbs)

Expected Lifetime:
The lifter has an expected lifetime of 30000 cycles (Max load) or 10 years, whichever occurs first.

Service is needed when after 10000 lifts with max load (SWL).





Produkto galerija




LINAK




Nova 500 NG
Prod.nr 16030201
IPX4
Int: 10%, max 2 min/18 min
Internally powered equipment
Max: 180 kg / 395 lbs
Tested
etac
SN 3P4624
Max 180 kg
Item no 16030201



LINAK


STOP













Technical Data

Safe Working Load (SWL)
180 kg (395 lbs)
Weight of unit
Total weight: 46 kg (101 lbs)
Chassis/Base: 13 kg (28½ lbs)
Lifting column/Mast: 23 kg (51 lbs)
Footrest incl. leg support: 10 kg (22 lbs)
Operating voltage:
24V DC
Power supply:
Battery power
Power consumption:
10A
Protection class:
Motor IPX4
Electrical box IPX4
Hand control IPX4
Sound volume:
53 dBA
Operating forces button
max 5 N
Material:
Powder-coated steel, Plastic
Turning radius:
approx. 110 cm (43½")
Number of lifts with fully charged battery:
80 lifts (80 kg / 175 lbs)
Expected Lifetime:
The lifter has an expected lifetime of 30000 cycles (Max load) or 10 years, whichever occurs first.

Service is needed when after 10000 lifts with max load (SWL).

